

3P Series 70/28



**WEED CONTROL
WITH 100%
HOT WATER**

**> Best value
for money**



**> No impact on
the environment
and sustainable**



**> Suitable for
all surfaces**



WAVE WEED CONTROL

All things considered the best in weed control.

Advantages WAVE 3P Series 70/28

- Environment-friendly, efficient, effective, durable
- Proven technology
- Suitable for tractors above 30 hp
- Choice of hydraulic or PTO drive
- 100% water, no additions
- Cleaning function (two-man operation possible)
- Dosing unit 1.40 metres optional
- Dosing unit Fast Forward (60 cm) optional
- Control possible on every type of (semi-permeable) paved surface
- Electronic temperature control (98 ° degrees)
- No foam additive needed (cost-cutting)
- No fire hazard, operation right up to the outer wall possible
- No harm or damage to paved surfaces or street
- Ergonomic and light-weight hand-held lances and hoses
- Adjustable anti-scale pump to prevent limescale deposits
- Use of surface water possible
- Use possible under plants and in tree surrounds
- Economical consumption of water and energy through efficient control of burner, precise dosing

Standard specifications

- Capacity: 28 litres of hot water per minute
- Capacity: 70 ha per year
- 3,750 - 5,750 m² per day
- Drive: hydraulic (30 l/180 bar) or PTO
- Heating: diesel
- Operating width manual operation: 20 – 80 cm
- Operating width dosing unit: 140 cm / 60 cm
- Working pressure weed control: 0 - 2 bar
- Operating speed: 0.8 – 3.5 kph (with low weed cover)
- Transport speed: dependent on tractor
- Water temperature: around 98 ° degrees Celsius at the lance
- Cleaning function: up to 90 bar (water temperature adjustable)
- Burners: 2 (diesel)
- Emission class high efficiency heating boilers: > Euro 6
- Capacity of water tank: 1,000 litres
- Burners tank capacity: 70 litres
- Temperature control: electronic (fully automatic)
- Colour: Ral 5010 (base), Ral 9006 (hoods)
- Surface water pump with high capacity incl filter set: optional
- Reels: 2 with 15-metre hose
- Hose extension: up to 60 metres optional (not on reel)
- Swivel castors for weight reduction: optional
- Heat exchanger: optional
- Noise level: low
- Anti-scale system: adjustable dosing pump
- Capacity of anti-scale liquid supply: 5 litres
- Dimensions (l*w*h): 133*155*208 (including wheels)
- Weight: around 940 kg



WAVE Europe B.V.
Turbinestraat 16A • 3903 LW Veenendaal
The Netherlands

+31 (0)318 469799 • +31 (0)318 469998
info@waveweedercontrol.eu • www.waveweedercontrol.eu